DAMIC-M activities at LSM in 2021 and 2022

Radomir Smida

smida@kicp.uchicago.edu

LSM Users Meeting, 14 Jan 2021





Outline

- Activities in 2021
 - Cleanroom
 - Our first detector at LSM
- Steps toward the full-scale DAMIC-M detector
- Plan for 2022

• Many thanks to the whole LSM team!




Cleanroom

- Between SuperNEMO and PARTAGe room.
- Main room is 4.2×4.7 m² and ISO 5, gowning room is 4.2×1.4 m² and ISO 6. Received in Feb and cooling issue addressed in July 2021. • Many thanks to Christophe and Thierry for their help.
- - Cleaned by an external company and ourself.
- Radon level measured with Durridge RAD7: (7.8 +/- 3.0) Bq/m3.









Cleanroom

• Low Background Chamber (LBC) is there now.



Dec 20

Low Background Chamber (LBC) Objectives



LBC will be a detector at LSM equipped with two single-electron resolution CCDs. Its objectives are as follows:

- each with 6k×4k pixels and 8.9 g.


The detector built by DAMIC-M Collaboration at LSM. We have learned a lot about working at LSM and this lesson will help us during the construction of the DAMIC-M detector.

2. A detector with the background level as low as few d.r.u. (material, cleaning and assembling procedures, simulations, etc.). This level will be lower than was in the DAMIC@SNOLAB detector. We want to be 10x better with DAMIC-M.

3. Detailed characterization of selected DAMIC-M CCDs in lowbackground environment. Our goal is to measure the dark current, ³²Si rate in the bulk, background in the backside layer, etc.

4. Science at low energies in silicon target with single-electron resolution CCDs. We aim to get 1 kg-day exposure. Two CCDs,

LBC Science Reach




6

0.05 kg-day 1 kg-day 40 kg-day 400 kg-day

> Benchmark models for scalar & fermion hidden-sector DM particle

LBC Assembly

- Took place from October to December 2021.
- Assembly took 11 weeks at LSM (ca. 1200 FTE hours).
- We are grateful for our help provided by LSM and also SuperNEMO and Edelweiss. \bullet












DAQ and slow control system, ...

CCDs in the LBC cryostat








LBC Status


- The detector works very well (vacuum, cooling, slow control, CCDs, etc.),
- The detector has been fully operated remotely since the mid December, \bullet

Refresh time: 3m	<u>Plots</u>		<u>catter</u>	Sys Log	<u>Runs</u>	<u>Users</u>	<u>Alarms</u>	Config
Select All		Cryocooler:		egacy:	PDU:		erSupply:	
						22:14:	54. Sensors	values in y
CryoTelGT 1	arget temperatu			e (Temp_T	arget)			
	200	0.00	J					
		(K)						
Reje	ct temperature of			ct_Temp)				
	39	.330	h					
		(C)						
Pre	essure of LBC cry	yostat (Press	ure_Ga	uge_1)				
	7.2	90e-	6					
		(mbar)						
F	Rotation Speed of	Pump (Rota	tion_s	peed)				
	9.00	03e+	4					
		(rpm)						
Ra	mprate of 100W		prate_	_100W)				
	1.	.000						
	(K/min)						
	Temperature	sensor A (Te	emp_A)				
	11:	5.000)					
		(K)						
	Temperature	sensor C (Te	emp_C)				
	117	7.08						
		(K)						



LBC Status

- The detector works very well (vacuum, cooling, slow control, CCDs, etc.),
- The detector has been fully operated remotely since the mid December,
- We are still in a commissioning phase
 - Both 6k×4k-pixel CCDs are working. We have reached noise below 5 e⁻ rms. The resolution is 0.14 e⁻ with 1000-skip readout (i.e. non-destructive, repetitive measurement
 - of the pixel charge).
 - We are reducing the dark current to reach our target value $< 10^{-3} e^{-1}/pix/day = 10^{-21} e^{-1}/cm^{2}$. ullet



LBC Plan for 2022

Work activities requiring our presence at LSM

To start our first science run:

- 1. Set up the readout system for the second CCD and the CompactRIO controller in February,
- 2. Temporary installation of the external shielding in February/March,

Both activities will 3 FTE for 3 weeks.

Improvements of LBC:


- 3. Modify the support structure and external shielding in March/April,
- 4. Install electro-formed copper parts from Canfranc in April.

Both activities will require 3 FTE for 4 weeks.

With these improvements, we plan to take science data remotely for months. Our presence will be only for monitoring and trouble shooting.


DAMIC-M Preparation

Packaging and Testing pre-production CCDs, format 6k×1.5k pixels



Pre-production CCD package


We are getting ready for the CCD production




Vacuum chamber with four CCDs

DAMIC-M Preparation

Moving forward with the Detector design








Array with 208 CCDs

DAMIC-M Preparation

Electronics under development






Heat exchanger will require ca. 1 kg/h of liquid N₂ at LSM

Silicon pitch adapter CCD mock-up


Heat exchanger mock-up







Schedule for 2022




Questions

- 1. Does our schedule fit the LSM plan?
- 2. What is the construction schedule of the new BINGO cleanroom?
- 3. Can we get nitrogen gas or radon-free air for a cabinet with CCDs?
- 4. Is it feasible to have ~1 kg/h of liquid nitrogen for the cooling of the full-scale DAMIC-M detector?

DAMIC-M Collaboration

DAMIC-M Collaboration







European Research Council stablished by the European Commission







FONDS NATIONAL SUISSE SCHWEIZERISCHER NATIONALFONDS FONDO NAZIONALE SVIZZERO SWISS NATIONAL SCIENCE FOUNDATION